



SMTPMaster Email Statistics Documentation

Documentation for Email-Statistics

This guide explains how to authenticate, enable access, read response bodies, paginate logs, and fetch the APIs from Python, Go, PHP, Laravel, and Java.

Quick Summary- Email Statistics:

GET /user-email-stats - aggregate delivered, bounce, hard bounce, soft bounce, and total sent counts.

Base URL :

Use your production backend domain as the base URL.

- <https://api.smtpmaster.com/api/user-email-stats>

Authentication:

Use the API key in the request header.

X-API-Key: YOUR_API_KEY

Accept:application/json

- The user must have an active plan. Expired, upcoming, inactive, suspended, and canceled plans are rejected

Where Can You Find the API Key?

After logging in to <https://app.smtpmaster.com/>, navigate to the **Email Config** section. There, you will find the Sending API option, where you can access the API key required for integration.

Note: If the API option is not visible in your account, please contact the SMTPMaster Support Team for assistance.

Endpoint: Get User Email Statistics

GET /user-email-stats

Returns aggregate counts.

Query parameters

- date - conditional. Single date in YYYY-MM-DD format. Use this alone; do not send start_date or end_date.

- start_date - conditional. Range start date in YYYY-MM-DD format. Required when end_date is present.

- end_date - conditional. Range end date in YYYY-MM-DD format. Required when start_date is present and must be after or equal to start_date.

Request examples

GET /user-email-stats?date=2026-08-11

GET /user-email-stats?start_date=2026-08-01&end_date=2026-08-11

Successful response body

```
{
  "success": true,
  "user_name": "John Doe",
  "date_filter": {
    "type": "date_range",
    "start_date": "2026-08-01",
    "end_date": "2026-08-11"
  },
  "stats": {
    "total_sent": 12450,
    "total_delivered": 12000,
    "total_bounce": 450,
    "hard_bounce": 120,
    "soft_bounce": 330
  }
}
```

Fetch Examples

Python

```
import requests
```

```
BASE_URL = "https://api.smtpmaster.com/api/"
X-API-Key= "YOUR_API_KEY"
headers = {"X-API-Key": API_KEY, "Accept": "application/json"}
```

```
stats = requests.get(
    f"{BASE_URL}/user-email-stats",
    headers=headers,
    params={"date": "2026-08-11"},
    timeout=30,
)
print(stats.status_code)
print(stats.json())
```

Go

The following Go example retrieves email statistics for a specific date.

```
package main

import (
    "fmt"
    "io"
    "net/http"
)

func main() {
    url := "https://api.smtpmaster.com/api/user-email-stats?date=2026-08-11"

    req, err := http.NewRequest("GET", url, nil)
    if err != nil {
        panic(err)
    }

    req.Header.Set("api_key", "YOUR_API_KEY")
    req.Header.Set("Accept", "application/json")
```

```

res, err := http.DefaultClient.Do(req)
if err != nil {
    panic(err)
}
defer res.Body.Close()
body, err := io.ReadAll(res.Body)
if err != nil {
    panic(err)
}
fmt.Println("Status Code:", res.StatusCode)
fmt.Println(string(body))
}

```

Replace YOUR_API_KEY with the API key available in your SMTPMaster account.

PHP

The following PHP example retrieves Email Stats for a specific date.

```
<?php
```

```
$url = "https://api.smtpmaster.com/api/user-email-stats?date=2026-08-11";
```

```
$ch = curl_init($url);
```

```

curl_setopt_array($ch, [
    CURLOPT_RETURNTRANSFER => true,
    CURLOPT_HTTPHEADER => [
        "Accept: application/json",
        "X-API-Key: YOUR_API_KEY",
    ],
]);

```

```
$response = curl_exec($ch);
```

```
$status = curl_getinfo($ch, CURLINFO_HTTP_CODE);
```

```
curl_close($ch);
```

```
echo "Status Code: " . $status . PHP_EOL;
```

```
echo $response . PHP_EOL;
```

For a date range, use:

```

https://api.smtpmaster.com/api/user-email-stats?start_date=2026-08-
01&end_date=2026-08-11

```

Laravel

Laravel applications can retrieve Email Stats using Laravel's HTTP client.

```
<?php
```

```
use Illuminate\Support\Facades\Http;
```

```
$response = Http::withHeaders([  
    "Accept" => "application/json",  
    "X-API-Key" => config("services.smtpmaster.api_key"),  
])->get("https://api.smtpmaster.com/api/user-email-stats", [  
    "start_date" => "2026-08-01",  
    "end_date" => "2026-08-11",  
]);
```

```
if ($response->successful()) {  
    $stats = $response->json("stats");
```

```
    // Example:
```

```
    // $stats["total_sent"]
```

```
    // $stats["total_delivered"]
```

```
    // $stats["total_bounce"]
```

```
    // $stats["hard_bounce"]
```

```
    // $stats["soft_bounce"]
```

```
} else {
```

```
    logger()->warning("SMTPMaster Email Stats API failed", [  
        "status" => $response->status(),
```

```
        "body" => $response->json(),
```

```
    ]);
```

```
};
```

Store the API key securely in your application configuration or environment file instead of writing the key directly into your source code.

Java

The following Java example retrieves Email Stats for a specific date.

```
import java.net.URI;
import java.net.http.HttpClient;
import java.net.http.HttpRequest;
import java.net.http.HttpResponse;

public class SmtplibMasterEmailStatsExample {

    public static void main(String[] args) throws Exception {

        HttpRequest request = HttpRequest.newBuilder()
            .uri(URI.create(
                "https://api.smtplibmaster.com/api/user-email-stats?date=2026-08-11"
            ))
            .header("Accept", "application/json")
            .header("X-API-Key", "YOUR_API_KEY")
            .GET()
            .build();

        HttpResponse<String> response = HttpClient.newHttpClient()
            .send(request, HttpResponse.BodyHandlers.ofString());

        System.out.println("Status Code: " + response.statusCode());
        System.out.println(response.body());
    }
}
```

Replace YOUR_API_KEY with your SMTPLibMaster API key.

Understanding the Email Stats Response

A successful request returns aggregated email statistics for the selected date or date range.

Example response:

```
{
  "success": true,
  "user_name": "John Doe",
  "date_filter": {
    "type": "date_range",
    "start_date": "2026-08-01",
    "end_date": "2026-08-11"
  },
  "stats": {
    "total_sent": 12450,
    "total_delivered": 12000,
    "total_bounce": 450,
    "hard_bounce": 120,
    "soft_bounce": 330
  }
}
```

Response Fields

total_sent

Total number of emails sent during the selected period.

total_delivered

Total number of emails successfully delivered.

total_bounce

Total number of bounced emails.

hard_bounce

Emails that failed permanently, such as messages sent to invalid or nonexistent addresses.

soft_bounce

Emails that experienced a temporary delivery failure.

Common Error Responses

The Email Stats API may return the following HTTP errors.

401 — Invalid API Credentials

```
{
  "success": false,
  "message": "Invalid API credentials"
}
```

Check that the API key is correct and included in the request header.

403 — Email Stats API Disabled

```
{
  "success": false,
  "message": "User email stats API is disabled by admin"
}
```

The Email Stats API is not currently enabled for the account. Contact SMTPMaster Support for assistance.

403 — Active Paid Plan Required

```
{
  "success": false,
  "message": "Active paid plan required"
}
```

The account does not currently meet the plan requirement for API access.

422 — Validation Failed

```
{
  "success": false,
  "message": "Validation failed",
  "errors": {
    ...
  }
}
```

This usually means one or more request parameters are missing or invalid. Check the date format and date-range parameters.

Dates must use:

YYYY-MM-DD

When requesting a range, both start_date and end_date must be provided, and end_date must be greater than or equal to start_date.

500 – Unexpected Error

```
{
  "success": false,
  "message": "Unexpected error occurred",
  "error": "...
}
```

An unexpected server-side error occurred. Try the request again or contact SMTPMaster Support if the problem continues.

Important Notes

- Use the API Key in every API request.
- Always include Accept: application/json.
- Use only the /user-email-stats endpoint for Email Stats.
- Use date when requesting statistics for one specific day.
- Use start_date and end_date when requesting statistics for a date range.
- Do not use date together with start_date or end_date.
- API access requires the applicable active plan and Email Stats API permission.
- Never expose your API key in frontend or client-side code.

For More Information Visit at : smtpmaster.com

Contact : +91 74396 80211

Email : info@smtpmaster.com

